

```
### Basic configuration
### *****

# Uncomment one of these if you want to allow remote clients to
# connect:

# proxyAddress = "::0"          # both IPv4 and IPv6
# proxyAddress = "0.0.0.0"     # IPv4 only

proxyAddress = "127.0.0.1"
proxyPort = 8118

# If you do that, you'll want to restrict the set of hosts allowed to
# connect:

# allowedClients = "127.0.0.1, 134.157.168.57"
# allowedClients = "127.0.0.1, 134.157.168.0/24"

allowedClients = 127.0.0.1
allowedPorts = 1-65535

# Uncomment this if you want your Polipo to identify itself by
# something else than the host name:

proxyName = "localhost"

# Uncomment this if there's only one user using this instance of Polipo:

cacheIsShared = false

# Uncomment this if you want to use a parent proxy:

# parentProxy = "squid.example.org:3128"

# Uncomment this if you want to use a parent SOCKS proxy:
```

```
socksParentProxy = "localhost:9050"
```

```
socksProxyType = socks5
```

```
### Memory
```

```
### *****
```

```
# Uncomment this if you want Polipo to use a ridiculously small amount  
# of memory (a hundred C-64 worth or so):
```

```
# chunkHighMark = 819200
```

```
# objectHighMark = 128
```

```
# Uncomment this if you've got plenty of memory:
```

```
# chunkHighMark = 50331648
```

```
# objectHighMark = 16384
```

```
chunkHighMark = 67108864
```

```
### On-disk data
```

```
### *****
```

```
# Uncomment this if you want to disable the on-disk cache:
```

```
diskCacheRoot = ""
```

```
# Uncomment this if you want to put the on-disk cache in a  
# non-standard location:
```

```
# diskCacheRoot = "~/polipo-cache/"
```

```
# Uncomment this if you want to disable the local web server:
```

```
localDocumentRoot = ""
```

```
# Uncomment this if you want to enable the pages under /polipo/index?  
# and /polipo/servers?. This is a serious privacy leak if your proxy  
# is shared.
```

```
# disableIndexing = false  
# disableServersList = false
```

```
disableLocalInterface = true  
disableConfiguration = true
```

```
### Domain Name System
```

```
### *****
```

```
# Uncomment this if you want to contact IPv4 hosts only (and make DNS  
# queries somewhat faster):
```

```
#
```

```
# dnsQueryIPv6 = no
```

```
# Uncomment this if you want Polipo to prefer IPv4 to IPv6 for
```

```
# double-stack hosts:
```

```
#
```

```
# dnsQueryIPv6 = reluctantly
```

```
# Uncomment this to disable Polipo's DNS resolver and use the system's  
# default resolver instead. If you do that, Polipo will freeze during  
# every DNS query:
```

```
dnsUseGethostbyname = yes
```

```
### HTTP
```

```
### ****
```

```
# Uncomment this if you want to enable detection of proxy loops.
```

```
# This will cause your hostname (or whatever you put into proxyName
```

```
# above) to be included in every request:
```

```
disableVia = true
```

```
# Uncomment this if you want to slightly reduce the amount of  
# information that you leak about yourself:
```

```
# censoredHeaders = from, accept-language  
# censorReferer = maybe
```

```
censoredHeaders = from,accept-language,x-pad,link  
censorReferer = maybe
```

```
# Uncomment this if you're paranoid. This will break a lot of sites,  
# though:
```

```
# censoredHeaders = set-cookie, cookie, cookie2, from, accept-language  
# censorReferer = true
```

```
# Uncomment this if you want to use Poor Man's Multiplexing; increase  
# the sizes if you're on a fast line. They should each amount to a few  
# seconds' worth of transfer; if pmmSize is small, you'll want  
# pmmFirstSize to be larger.
```

```
# Note that PMM is somewhat unreliable.
```

```
# pmmFirstSize = 16384  
# pmmSize = 8192
```

```
# Uncomment this if your user-agent does something reasonable with  
# Warning headers (most don't):
```

```
# relaxTransparency = maybe
```

```
# Uncomment this if you never want to revalidate instances for which  
# data is available (this is not a good idea):
```

```
# relaxTransparency = yes
```

```
# Uncomment this if you have no network:
```

```
# proxyOffline = yes
```

```
# Uncomment this if you want to avoid revalidating instances with a
```

```
# Vary header (this is not a good idea):
```

```
# mindlesslyCacheVary = true
```

```
# Suggestions from Incognito configuration
```

```
maxConnectionAge = 5m
```

```
maxConnectionRequests = 120
```

```
serverMaxSlots = 8
```

```
serverSlots = 2
```

```
tunnelAllowedPorts = 1-65535
```

```
#forward-socks4a / localhost:9050 .
```